

# TOMEI Camshaft Spec Card

PART NAME	PROCAM			ENGINE	RB20DE(T)		
-----------	--------	--	--	--------	-----------	--	--

PART NUMBER	SET	-	IN	1417260092	EX	1418260092
-------------	-----	---	----	------------	----	------------

GRIND	IN	260° / 9.25mm	SOLID	BACE	IN	Φ 29.0	ROCKER ARM RATIO*	VALVE CLEARANCE IN	0.45
	EX	260° / 9.25mm	SOLID		CIRCLE(Φ)	EX			Φ 29.0

LIFT	IN	@CAM 9.25mm	@VALVE 8.80mm	LOBE	IN	110.0
	EX	@CAM 9.25mm	@VALVE 8.87mm		CENTER(°)	EX

\* ALL LIFTS ARE BASED ON ZERO LASH AND THORETICAL ROCKER ARM RATIOS

CAM TIMING		OPENS(°)		CLOSES(°)		Actual Duration @ Opening(°)
Actual Duration	IN	BTDC	20.0	ABDC	60.0	260.0
Valve Lift	EX	BBDC	65.0	ATDC	15.0	260.0





Values shown are, from start to the end of actual duration. (Excluding the ramp values)

CAM TIMING		OPENS(°)		CLOSES(°)		TOTAL DURATION(°)
at 1mm	IN	BTDC	4.0	ABDC	44.5	228.5
Valve Lift	EX	BBDC	50.0	ATDC	0.5	230.5

Values are of actual duration from start to end of 1mm value points. (Excluding ramp values)

CAM TIMING		OPENS(°)		CLOSES(°)		TOTAL DURATION(°)
at 0.05"	IN	BTDC	2.0	ABDC	42.5	224.5
Valve Lift	EX	BBDC	48.0	BTDC	1.5	226.5

Values are of actual duration from start to end of 0.05" value points. (Excluding ramp values)



REQUIRED VALVE SPRING SPEC	
NOMAL HEIGHT (mm)	41.0
SET LENGTH (mm)	35.0
LIFT LENGTH (mm)	25.0
COMPRESSED HEIGHT (mm)	24.0
SET LOAD (kgf)	24.2 ± 7%
LIFT LOAD (kgf)	80.6 ± 7%
TOMEI PART NUMBER	13203R800

REQUIRED PARTS	
PRODUCT NAME	TOMEI PART NUMBER
SOLID VALVE LIFTERS	163006
SHIMS	
ADJUSTABLE CAM PULLEYS IN	152009
ADJUSTABLE CAM PULLEYS EX	152010