

# TOMEI Camshaft Spec Card

The Engine Specialist

PART NAME **PONCAM/PROCAM** ENGINE **VQ35DE EARLY (-05.09)**

PART NUMBER SET **TA301A-NS04C** IN **TA301C-NS04C** EX **TA301E-NS04C**

GRIND	IN	282° /11.30mm	-
	EX	282° /11.00mm	-

LIFT	IN	@CAM 11.30mm	@VALVE 11.00mm
	EX	@CAM 11.00mm	@VALVE 10.67mm

LOBE CENTER(°)	IN	125.0
	EX	112.0

BASE CIRCLE	IN	Φ35.4
	EX	Φ35.4

VALVE CLEARANCE WHEN COLD	IN	0.30
	EX	0.33

ROCKER ARM RATIO*	-
-------------------	---

\* ALL LIFTS ARE BASED ON ZERO LASH AND THORETICAL ROCKER ARM RATIOS

CAM TIMING		OPENS(°)		CLOSES(°)		Actual Duration @ Opening (°)
Actual Duration Valve Lift	IN	BTDC	15.0	ABDC	87.0	282.0
	EX	BBDC	72.0	ATDC	30.0	282.0


Values shown are, from start to the end of actual duration. (Excluding the ramp values)

CAM TIMING		OPENS(°)		CLOSES(°)		TOTAL DURATION(°)
at 1mm Valve Lift	IN	ATDC	1.0	ABDC	69.0	248.0
	EX	BBDC	56.0	ATDC	12.0	248.0

Values are of actual duration from start to end of 1mm value points. (Excluding the ramp values)




CAM TIMING		OPENS(°)		CLOSES(°)		TOTAL DURATION(°)
at 0.05" Valve Lift	IN	ATDC	3.0	ABDC	67.0	248.0
	EX	BBDC	54.0	ATDC	10.0	240.0

Values are of actual duration from start to end of 0.05" value points. (Excluding the ramp values)



REQUIRED VALVE SPRING SPEC	
NORMAL HEIGHT	49.1
SET LENGTH	37.0
LIFT LENGTH	26.0
COMPRESSED HEIGHT	25.0
SET LOAD	24.0 ±6%
LIFT LOAD	56.8 ±6%
PART NUMBER	TA304A-NS02A

REQUIRED PARTS	
PRODUCT NAME	PART NUMBER



Dowel pin position when first cam lobe is pointing upwards.  
IN

EX

# TOMEI Camshaft Spec Card

The Engine Specialist

品名 **PONCAM/PROCAM** 適合 **VQ35DE EARLY (-05.09)**

品番 **SET TA301A-NS04C IN TA301C-NS04C EX TA301E-NS04C**

スペック	IN	282° /11.30mm	-
	EX	282° /11.00mm	-

リフト	IN	@CAM 11.30mm	@VALVE 11.00mm
	EX	@CAM 11.00mm	@VALVE 10.67mm

初期設定 中心角(°)	IN	125.0
	EX	112.0

ベース円	IN	Φ35.4
	EX	Φ35.4

冷間時 バルブクリアランス	IN	0.30
	EX	0.33

ロッカーアームレシオ*	-
-------------	---

\* すべてのリフト値はラッシュアジャスターが動作していない時、およびロッカーアームレシオから計算した理論値です。

カムタイミング		OPENS(°)		CLOSES(°)		Actual Duration @ Opening (°)
有効作用角 バルブリフト	IN	BTDC	15.0	ABDC	87.0	282.0
	EX	BBDC	72.0	ATDC	30.0	282.0


ランプ部を除いた有効作用角の始点と終点の数値

カムタイミング		OPENS(°)		CLOSES(°)		TOTAL DURATION(°)
1mm バルブリフト	IN	ATDC	1.0	ABDC	69.0	248.0
	EX	BBDC	56.0	ATDC	12.0	248.0

ランプ部を含めたバルブの開き始めと閉じ終わりから1mmの点での数値




カムタイミング		OPENS(°)		CLOSES(°)		TOTAL DURATION(°)
0.05" バルブリフト	IN	ATDC	3.0	ABDC	67.0	248.0
	EX	BBDC	54.0	ATDC	10.0	240.0

ランプ部を含めたバルブの開き始めと閉じ終わりから0.05インチの点での数値



推奨バルブスプリング	
自由長	49.1
セット長	37.0
リフト長	26.0
密着長	25.0
セット荷重	24.0 ±6%
リフト荷重	56.8 ±6%
品番	TA304A-NS02A

必要部品	
製品名	品番



第1カム山をトップ位置にした際の  
ノックピン位置

IN

EX